

Greedy Algorithms for Multi-Queue Buffer Management with Class Segregation

TOSHIYA ITOH
titoh@ip.titech.ac.jp

Imaging Science & Engineering Laboratory
Tokyo Institute of Technology

SEIJI YOSHIMOTO
yoshimoto.s.aa@m.titech.ac.jp
Department of Computer Science
Tokyo Institute of Technology

Abstract: In this paper, we focus on a multi-queue buffer management in which packets of different values are segregated in different queues. Our model consists of m packet values and m queues. Recently, Al-Bawani and Souza (CoRR abs/1103.6049v2 [cs.DS] 19 Sep 2011) presented an online multi-queue buffer management algorithm **Greedy** and showed that it is 2-competitive for the general m -valued case, i.e., m packet values are $0 < v_1 < v_2 < \dots < v_m$, and it is $(1 + v_1/v_2)$ -competitive for the two-valued case, i.e., two packet values are $0 < v_1 < v_2$. For the general m -valued case, let $c_i = (v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}) / (v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j})$ for $1 \leq i \leq m-1$, and let $c_m^* = \max_i c_i$. In this paper, we precisely analyze the competitive ratio of **Greedy** for the general m -valued case, and show that the algorithm **Greedy** is $(1 + c_m^*)$ -competitive.

Key Words: Online Algorithms, Competitive Ratio, Buffer Management, Class Segregation, Quality of Service (QoS), Class of Service (CoS).

1 Introduction

Due to the burst growth of the Internet use, network traffic has increased year by year. This overloads networking systems and degrades the quality of communications, e.g., loss of bandwidth, packet drops, delay of responses, etc. To overcome such degradation of the communication quality, the notion of Quality of Service (QoS) has received attention in practice, and is implemented by assigning nonnegative numerical values to packets to provide them with differentiated levels of service (priority). Such a packet value corresponds to the predefined Class of Service (CoS). In general, switches have several number of queues and each queue has a *buffer* to store arriving packets. Since network traffic changes frequently, switches need to control arriving packets to maximize the total priorities of transmitted packets, which is called *buffer management*. Basically, switches have no knowledge on the arrivals of packets in the future when it manages to control new packets arriving to the switches. So the decision made by buffer management algorithm can be regarded as an *online algorithm*, and in general, the performance of online algorithms is measured by *competitive ratio* [8]. Online buffer management algorithms can be classified into two types of queue management (one is *preemptive* and the other is *nonpreemptive*). Informally, we say that an online buffer management algorithm is preemptive if it is allowed to discard packets buffered in the queues on the arrival of new packets; nonpreemptive otherwise (i.e., all packets buffered in the queues will be eventually transmitted).

1.1 Multi-Queue Buffer Management

In this paper, we focus on a multi-queue model in which packets of different values are segregated in different queues (see, e.g., [11], [17]). Our model consists of m packet values and m queues¹.

¹ In general, we can consider a model of m packet values and n queues (with $m \neq n$), but in this paper, we deal with only a model of m packet values and m queues.

Let $\mathcal{V} = \{v_1, v_2, \dots, v_m\}$ be the set of m nonnegative *packet values*, where $0 < v_1 < v_2 < \dots < v_m$, and let $\mathcal{Q} = \{Q_1, Q_2, \dots, Q_m\}$ be the set of m queues. A packet of value $v_i \in \mathcal{V}$ is referred to as a v_i -*packet*, and a queue storing v_i -packets is referred to as a v_i -*queue*. Without loss of generality, we assume that $Q_i \in \mathcal{Q}$ is a v_i -queue for each $i \in [1, m]^2$. Each $Q_i \in \mathcal{Q}$ has a capacity $B_i \geq 1$, i.e., each $Q_i \in \mathcal{Q}$ can store up to $B_i \geq 1$ packets. Since all packets buffered in queue $Q_i \in \mathcal{Q}$ have the same value $v_i \in \mathcal{V}$, the order of transmitting packets is irrelevant.

For convenience, we assume that time is discretized into slot of unit length. Packets arrive over time and each arriving packet is assigned with a unique (nonintegral) arrival time, a value $v_i \in \mathcal{V}$, and its destination queue $Q_i \in \mathcal{Q}$ (as we have assumed, $Q_i \in \mathcal{Q}$ is a v_i -queue). We use $\sigma = \langle e_0, e_1, e_2, \dots \rangle$ to denote a sequence of *arrive events* and *send events*, where an arrive event corresponds to the arrival of a new packet and a send event corresponds to the transmission of a packet buffered in queues at integral time (i.e., the end of time slot). An online (multi-queue) buffer management algorithm **Alg** consists of two phases: *admission* phase *scheduling* phases. In the admission phase, **Alg** must decide on the arrival of a packet whether to accept or reject the packet without any knowledge on the future arrivals of packets (if **Alg** is preemptive, then it may discard packets buffered in queues in the admission phase). In the scheduling phase, **Alg** chooses one of the nonempty queues at send event and exactly one packet is transmitted out of the queue chosen. Since all packets buffered in the same queue have the same value, preemption does not make sense in our model. Thus a packet accepted must eventually be transmitted.

We say that an (online and offline) algorithm is *diligent* if (1) it must accept a packet arriving to its destination queue when the destination queue has vacancies, and (2) it must transmit a packet when it has nonempty queues. It is not difficult to see that any nondiligent algorithm can be transformed to a diligent algorithm without decreasing its benefit (sum of values of transmitted packets). Thus in this paper, we focus on only diligent algorithms.

1.2 Main Results

Al-Bawani and Souza [2] recently presented an online multi-queue buffer management algorithm **Greedy** and showed that it is 2-competitive for the general m -valued case, i.e., m packet values are $0 < v_1 < v_2 < \dots < v_m$, and $(1 + v_1/v_2)$ -competitive for the two-valued case, i.e., $m = 2$.

For the general m -valued case, let $c_m^* = \max_i c_i$, where for each $1 \leq i \leq m - 1$,

$$c_i = \frac{v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}}{v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}}.$$

In this paper, we precisely analyze the competitive ratio of **Greedy** for the general m -valued case, and show that the algorithm **Greedy** is $(1 + c_m^*)$ -competitive (see Theorem 4.1). Note that $c_m^* < 1$. Thus we have that $1 + c_m^* < 2$ and for the general m valued case, our results improves the known result that the algorithm **Greedy** is 2-competitive [2, Theorem 2.1].

For example, let us consider the case that $v_1 = 1, v_2 = 2$, and $v_{i+1} = v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}$ for each $i \in [2, m - 1]$. It is obvious that $0 < v_1 < v_2 < \dots < v_m$ and $c_m^* = \max_i c_i = 1/2$. Thus for those packet values, our result guarantees that the algorithm **Greedy** is 3/2-competitive, while the known result only guarantees that the algorithm **Greedy** is 2-competitive [2, Theorem 2.1].

² For any pair of integers $a \leq b$, let $[a, b] = \{a, a + 1, \dots, b\}$.

1.3 Related Works

The competitive analysis for the buffer management policies for switches were initiated by Aiello et al. [1], Mansour et al. [18], and Kesselman et al. [16], and the extensive studies have been made for several models (for comprehensive surveys, see, e.g., [4],[12],[15],[10],[13]).

The model we deal with in this paper can be regarded as the generalization of unit-valued model, where the switches consist of m queues of the same buffer size B and all packets have unit value, i.e., $v_1 = v_2 = \dots = v_m$. The following tables summarize the known results:

Table 1: Deterministic Competitive Ratio (Unit-Valued Multi-Queue Model)

Upper Bound			Lower Bound		
2	[6]	—	$2 - 1/m$	[6]	$B = 1$
1.889	[3]	$m \gg B$	$1.366 - \Theta(1/m)$	[6]	$B \geq 1$
1.857	[3]	$B = 2$	$\frac{e}{e-1} \approx 1.582$	[3]	—
$\frac{e}{e-1} \approx 1.582$	[5]	large B			

Table 2: Randomized Competitive Ratio (Unit-Valued Multi-Queue Model)

Upper Bound			Lower Bound		
$\frac{e}{e-1} \approx 1.582$	[6]	$B > \log m$	$1.46 - \Theta(1/m)$	[6]	$B = 1$
1.231	[9]	$m = 2$	1.466	[3]	large m
			1.231	[3]	$m = 2$

On the other hand, the model we deal with in this paper can be regarded as a special case of the general-valued multi-queue model where each of m FIFO queues can buffer at most B packets of different values. For the preemptive multi-queue buffer management, Azar and Richter [6] presented a $(4 + 2 \ln \alpha)$ -competitive algorithm for the general-valued case (packet values lie between 1 and α) and a 2.6-competitive algorithm for the two-valued case (packet values are $v_1 < v_2$, where $v_1 = 1$ and $v_2 = \alpha$). For the general-valued case, Azar and Richter [7] proposed a more efficient algorithm TRANSMIT-LARGEST HEAD (TLH) that is 3-competitive, which is shown to be $(3 - 1/\alpha)$ -competitive by Itoh and Takahashi [14].

2 Preliminaries

For a sequence σ' of arriving packets, we use $\sigma = \langle e_0, e_1, e_2, \dots \rangle$ to denote a sequence of arrive and send events. Notice that an arrive event corresponds to the arrival of a new packet (at non-integral time) and a send event corresponds to the transmission of a packet buffered in queues at integral time. The online algorithm **Greedy** works as follows: At send event, **Greedy** transmits a packet from the nonempty queue with highest packet value³, i.e., **Greedy** transmits a v_h -packet if v_h -queue is nonempty and all v_ℓ -queues are empty for $\ell \in [h + 1, m]$. At arrive event, **Greedy** accepts packets in its destination queue until the corresponding queue becomes full.

³ Since $Q_i \in \mathcal{Q}$ is a v_i -queue, such a nonempty queue with highest packet value is *unique* if it exists.

For an *online* algorithm Alg and a sequence σ of arrive and send events, we use $\text{Alg}(\sigma)$ to denote the *benefit* of the algorithm Alg on the sequence σ , i.e., the sum of values of packets transmitted by the algorithms Alg on the sequence σ . For a sequence σ of arrive and send events, we also use $\text{Opt}(\sigma)$ to denote the *benefit* of the *optimal offline* algorithm Opt on the sequence σ , i.e., the sum of values of packets transmitted by the optimal offline algorithm Opt that knows the entire sequence σ in advance. Our goal is to design an efficient (deterministic) online algorithm Alg that minimizes $\text{Opt}(\sigma)/\text{Alg}(\sigma)$ for any sequence σ .

At event e_i , let $A_h(e_i)$ and $A_h^*(e_i)$ be the total number of v_h -packets accepted by **Greedy** and **Opt** until the event e_i , respectively, $\delta_h(e_i)$ and $\delta_h^*(e_i)$ be the total number of v_h -packets transmitted by **Greedy** and **Opt** until the event e_i , respectively, and $q_h(e_i)$ and $q_h^*(e_i)$ be the total number of v_h -packets buffered in v_h -queue of **Greedy** and **Opt** just after the event e_i , respectively. It is immediate to see that for each $h \in [1, m]$ and each event e_i ,

$$A_h(e_i) = \delta_h(e_i) + q_h(e_i); \quad (1)$$

$$A_h^*(e_i) = \delta_h^*(e_i) + q_h^*(e_i). \quad (2)$$

For a sequence σ , let $A_h(\sigma)$ and $A_h^*(\sigma)$ be the total number of v_h -packets accepted by **Greedy** and **Opt** until the end of the sequence σ , respectively, $\delta_h(\sigma)$ and $\delta_h^*(\sigma)$ be the total number of v_h -packets transmitted by **Greedy** and **Opt** until the end of the sequence σ , respectively, and $q_h(\sigma)$ and $q_h^*(\sigma)$ be the number of v_h -packets buffered in v_h -queue of **Greedy** and **Opt** at the end of the sequence σ , respectively. It is immediate to see that $q_h(\sigma) = q_h^*(\sigma) = 0$ for each $h \in [1, m]$. So from Eqs. (1) and (2), it follows that $A_h(\sigma) = \delta_h(\sigma)$ and $A_h^*(\sigma) = \delta_h^*(\sigma)$ for each $h \in [1, m]$.

For the general m -valued case, Al-Bawani and Souza showed the following result on the number of packets accepted by **Greedy** and **Opt**, which is crucial in the subsequent discussions.

Lemma 2.1 [2, Lemma 2.2]: *For each $h \in [1, m]$, the following holds:*

$$\sum_{\ell=h}^m \{A_\ell^*(\sigma) - A_\ell(\sigma)\} \leq \sum_{\ell=h}^m A_\ell(\sigma).$$

Assume that in the sequence $\sigma = \langle e_0, e_1, e_2, \dots \rangle$, there exist $k \geq 1$ send events, and for each $j \in [0, k]$, let s_j be the j th send event, where $s_0 = e_0$ is an initial send event that transmits a null packet. For each $j \in [1, k]$, we use Σ_j to denote the set of arrive events between send event s_{j-1} and send event s_j , i.e., Σ_j consists of arrive events after send event s_{j-1} and before send event s_j . Notice that Σ_j could be an empty set.

3 Relationships Between Greedy and Opt

3.1 Number of Transmitted Packets

In this subsection, we investigate the relationships between the number of packets transmitted by **Greedy** and the number of packets transmitted by **Opt**. For each $h \in [1, m-1]$ and each event e_i , let $\xi_h(e_i) = \delta_h(e_i) + \dots + \delta_m(e_i) - \delta_h^*(e_i)$.

Claim 3.1: *For each $h \in [1, m-1]$ and each $j \in [2, k]$, if $q_h(s_{j-1}) + \dots + q_m(s_{j-1}) > 0$ (i.e., just after s_{j-1} , a nonempty v_ℓ -queue of **Greedy** with $\ell \in [h, m]$ exists), then $\xi_h(s_j) \geq \xi_h(s_{j-1})$.*

Proof: Since every $e_i \in \Sigma_j$ is arrive event, we have that for each $g \in [h, m]$, the number of packets buffered in v_g -queue does not decrease at each arrive event $e_i \in \Sigma_j$. Then from the assumption that $q_h(s_{j-1}) + \dots + q_m(s_{j-1}) > 0$, it follows that there exists an $\ell \in [h, m]$ such that v_ℓ -queue of **Greedy** is nonempty just before send event s_j . Thus from the definition of **Greedy**, it is immediate to see that for some $r \in [\ell, m]$, **Greedy** transmits a v_r -packet at send event s_j , which implies that $\delta_h(s_j) + \dots + \delta_m(s_j) = \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) + 1$. So we have that

$$\begin{aligned}\xi_h(s_j) &= \delta_h(s_j) + \dots + \delta_m(s_j) - \delta_h^*(s_j) \\ &\geq \{\delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) + 1\} - \{\delta_h^*(s_{j-1}) + 1\} \\ &= \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) - \delta_h^*(s_{j-1}) = \xi_h(s_{j-1}),\end{aligned}$$

where the inequality follows from the fact that $\delta_h^*(s_j) \leq \delta_h^*(s_{j-1}) + 1$. ■

Claim 3.2: For each $h \in [1, m-1]$ and each $j \in [1, k]$, if $q_h^*(s_{j-1}) = 0$ (i.e., just after s_{j-1} , v_h -queue of **Opt** is empty), then $\xi_h(s_j) \geq \xi_h(s_{j-1})$.

Proof: Let us consider the following cases: (1) v_h -queue of **Opt** is empty just before send event s_j and (2) v_h -queue of **Opt** is nonempty just before send event s_j . For the case (1), it is immediate to see that $\delta_h^*(s_j) = \delta_h^*(s_{j-1})$. So we have that

$$\begin{aligned}\xi_h(s_j) &= \delta_h(s_j) + \dots + \delta_m(s_j) - \delta_h^*(s_j) \\ &\geq \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) - \delta_h^*(s_{j-1}) = \xi_h(s_{j-1}),\end{aligned}$$

where the inequality follows from the fact that $\delta_h(s_j) + \dots + \delta_m(s_j) \geq \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1})$. For the case (2), there exists arrive event $e_i \in \Sigma_j$ such that a v_h -packet arrives, because of the assumption that v_h -queue of **Opt** is empty just after the send event s_{j-1} . Then from the definition of **Greedy**, it is easy to see that v_h -queue of **Greedy** is nonempty just before send event s_j and that at send event s_j , **Greedy** transmits a v_ℓ -packet with $\ell \in [h, m]$. This implies that $\delta_h(s_j) + \dots + \delta_m(s_j) = \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) + 1$. Thus it follows that

$$\begin{aligned}\xi_h(s_j) &= \delta_h(s_j) + \dots + \delta_m(s_j) - \delta_h^*(s_j) \\ &\geq \{\delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) + 1\} - \{\delta_h^*(s_{j-1}) + 1\} \\ &= \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) - \delta_h^*(s_{j-1}) = \xi_h(s_{j-1}),\end{aligned}$$

where the inequality follows from the fact that $\delta_h^*(s_j) \leq \delta_h^*(s_{j-1}) + 1$. ■

Lemma 3.1: For each $h \in [1, m-1]$ and each event e_i , $\xi_h(e_i) \geq 0$.

Proof: We show the lemma by induction on events e_i . It is obvious that $\xi_h(e_0) = 0$. For $t \geq 1$, assume that $\xi_h(e_i) \geq 0$ for each $i \in [0, t-1]$. If e_t is arrive event, then $\delta_\ell(e_t) = \delta_\ell(e_{t-1})$ for each $\ell \in [h, m]$ and $\delta_h^*(e_t) = \delta_h^*(e_{t-1})$. This implies that $\xi_h(e_t) = \xi_h(e_{t-1})$ and from the induction hypothesis, it follows that $\xi_h(e_t) = \xi_h(e_{t-1}) \geq 0$. Thus in the rest of the proof, we focus on only send events and show the lemma by induction on send events s_j .

Base Step: We show that $\xi_h(s_1) \geq 0$ at the first send event s_1 . Let us consider the following cases: (1) there exists arrive event $e_t \in \Sigma_1$ at which a v_ℓ -packet with $\ell \in [h, m]$ arrives and (2) there exists no arrive event $e_t \in \Sigma_1$ at which a v_ℓ -packet with $\ell \in [h, m]$ arrives. For the case (1), we have that v_ℓ -queue of **Greedy** is nonempty just before send event s_1 . So from the definition of **Greedy**, it follows that $\delta_h(s_1) + \dots + \delta_m(s_1) = 1$. Since $\delta_h^*(s_1) \leq 1$, this implies that $\xi_h(s_1) =$

$\delta_h(s_1) + \dots + \delta_m(s_1) - \delta_h^*(s_1) \geq 1 - 1 = 0$. For the case (2), it is immediate that $\delta_h(s_1) = \dots = \delta_m(s_1) = 0$ and $\delta_h^*(s_1) = 0$. Thus we have that $\xi_h(s_1) = \delta_h(s_1) + \dots + \delta_m(s_1) - \delta_h^*(s_1) = 0 - 0 = 0$.

Induction Step: For $t \in [2, k]$, assume that $\xi_h(s_j) \geq 0$ for each $j \in [0, t-1]$. Since $\delta_h(s_t) + \dots + \delta_m(s_t) \geq \delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1})$ and $\delta_h^*(s_t) \leq \delta_h^*(s_{t-1}) + 1$, we have that if $\xi_h(s_{t-1}) \geq 1$, then

$$\begin{aligned} \xi_h(s_t) &= \delta_h(s_t) + \dots + \delta_m(s_t) - \delta_h^*(s_t) \\ &\geq \delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1}) - \{\delta_h^*(s_{t-1}) + 1\} \\ &= \delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1}) - \delta_h^*(s_{t-1}) - 1 = \xi_h(s_{t-1}) - 1 \geq 0. \end{aligned}$$

Thus we assume that $\xi_h(s_{t-1}) = \delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1}) - \delta_h^*(s_{t-1}) = 0$. If $\delta_h^*(s_{t-1}) = 0$, then we have $\delta_h(s_{t-1}) = \dots = \delta_m(s_{t-1}) = 0$. From the definition of **Greedy**, it follows that for each $\ell \in [h, m]$, no v_ℓ -packets arrive until send event s_{t-1} , which implies that $q_h^*(s_{t-1}) = 0$. So from Claim 3.2 and the induction hypothesis, it follows that $\xi_h(s_t) \geq \xi_h(s_{t-1}) \geq 0$.

Assume that $\delta_h^*(s_{t-1}) = n > 0$ and we consider the following cases: (3) **Greedy** does not reject any v_h -packet that arrives until send event s_{t-1} ; (4) **Greedy** rejects v_h -packets that arrive until send event s_{t-1} . For the case (3), let n_h be the number of v_h -packets that arrive until send event s_{t-1} . It is obvious that $n_h \geq \delta_h^*(s_{t-1}) = n > 0$. If $q_h(s_{t-1}) > 0$, then from Claim 3.1 and the induction hypothesis, it follows that $\xi_h(s_t) \geq \xi_h(s_{t-1}) \geq 0$. Assume that $q_h(s_{t-1}) = 0$. Since $n_h > 0$ v_h -packets arrive until send event s_{t-1} , $q_h(s_{t-1}) = 0$, and **Greedy** does not reject any v_h -packet that arrives until send event s_{t-1} , we have that $\delta_h(s_{t-1}) = n_h$. If $\delta_h^*(s_{t-1}) < n_h$, then $\delta_h^*(s_{t-1}) < n_h \leq \delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1})$, which contradiction the assumption that $\delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1}) - \delta_h^*(s_{t-1}) = 0$. So we assume that $\delta_h^*(s_{t-1}) = n_h$. From Eq. (2) and the fact that $n_h \geq A_h^*(s_{t-1})$, it is immediate that $q_h^*(s_{t-1}) = A_h^*(s_{t-1}) - \delta_h^*(s_{t-1}) \leq n_h - n_h = 0$, i.e., $q_h^*(s_{t-1}) = 0$. So from Claim 3.2 and the induction hypothesis, it follows that $\xi_h(s_t) \geq \xi_h(s_{t-1}) \geq 0$.

For the case (4), consider the following subcases: (4.1) $q_h(s_{t-1}) > 0$; (4.2) $q_h(s_{t-1}) = 0$. For the subcase (4.1), it is obvious that $q_h(s_{t-1}) + \dots + q_m(s_{t-1}) > 0$. Thus from Claim 3.1 and the induction hypothesis, it follows that $\xi_h(s_t) \geq \xi_h(s_{t-1}) \geq 0$. For the subcase (4.2), let e_τ be the last arrive event at which a v_h -packet is rejected by **Greedy**. Assume that $e_\tau \in \Sigma_j$ for some $j \in [1, t-1]$, i.e., e_τ is arrive event between send event s_{j-1} and send event s_j . Notice that the v_h -queue of **Greedy** is *full* just before arrive event e_τ . This implies that v_h -queue of **Greedy** is *full* just before send event s_j . Let $L_h \geq 0$ be the total number of v_h -packets that arrive between send events s_j and s_{t-1} . Since $q_h(s_{t-1}) = 0$, **Greedy** must transmit $B_h + L_h$ v_h -packets from send event s_j to send event s_{t-1} . So it follows that $\delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1}) \geq \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) + B_h + L_h$. Assume that **Opt** transmits $K_h \geq 0$ v_h -packets at send events $s_j, \dots, s_{t-1}$, i.e., $\delta_h^*(s_{t-1}) = \delta_h^*(s_{j-1}) + K_h$. From the induction hypothesis that $\xi_h(s_{j-1}) \geq 0$, it follows that

$$\begin{aligned} \xi_h(s_{t-1}) &= \delta_h(s_{t-1}) + \dots + \delta_m(s_{t-1}) - \delta_h^*(s_{t-1}) \\ &\geq \{\delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) + B_h + L_h\} - \{\delta_h^*(s_{j-1}) + K_h\} \\ &= \delta_h(s_{j-1}) + \dots + \delta_m(s_{j-1}) - \delta_h^*(s_{j-1}) + B_h + L_h - K_h \\ &= \xi_h(s_{j-1}) + B_h + L_h - K_h \geq B_h + L_h - K_h. \end{aligned}$$

Note that $K_h \leq B_h + L_h$. If $K_h < B_h + L_h$, then it is immediate that $\xi_h(s_{t-1}) > 0$, which contradicts the assumption that $\xi_h(s_{t-1}) = 0$. So we have $K_h = B_h + L_h$, which implies that $q_h^*(s_{t-1}) = 0$. Thus from Claim 3.2 and the induction hypothesis, it follows that $\xi_h(s_t) \geq \xi_h(s_{t-1}) = 0$. ■

3.2 Number of Accepted Packets

In this subsection, we investigate the relationships between the number of packets accepted by **Greedy** and the number of packets accepted by **Opt**. In the rest of this paper, we use A_h and A_h^* instead of $A_h(\sigma)$ and $A_h^*(\sigma)$ respectively, when σ is clear from the context. For each $h \in [1, m]$, let $D_h = A_h^* - A_h$ and $S_h = A_h + A_{h+1} + \dots + A_m$.

The following lemma shows the relationship between the number of v_m -packets accepted by **Greedy** and the number of v_m -packets accepted by **Opt**, which is a straightforward generalization of the result due to Al-Bawani and Souza [2, Lemma 2.5].

Lemma 3.2: $A_m = A_m^*$.

Proof: By definition of **Greedy**, v_m -packet has priority at send event. Thus at any event e_i , the number of v_m -packets transmitted by **Greedy** is maximum, i.e., $A_m(e_i) \geq A_m^*(e_i)$.

Assume that at arrive event e_t , $A_m(e_t)$ becomes greater than $A_m^*(e_t)$ for the first time, which implies that at arrive event e_t , **Opt** rejects a v_m -packet but **Greedy** accepts a v_m -packet. Thus just before event e_t , v_m -queue of **Opt** is full but v_m -queue of **Greedy** has at least one vacancy. Since $A_m(e_{t-1}) = A_m^*(e_{t-1})$, there must exist send event e_τ (with $\tau \leq t-1$) at which **Opt** transmitted a v_ℓ -packet with $\ell \in [1, m-1]$, while the v_m -queue of **Opt** was not empty. Change the behavior of **Opt** at send event e_τ by transmitting a v_m -packet instead of the v_ℓ -packet. This yields an increase in the benefit of **Opt** and the v_m -packet rejected at arrive event e_t can be accepted. ■

The following lemma is a straightforward extension of the result by Al-Bawani and Souza [2, Lemma 2.6] and plays a crucial role in the subsequent discussions.

Lemma 3.3: For each $h \in [1, m-1]$, the following holds:

$$D_h = A_h^* - A_h \leq \sum_{\ell=h+1}^m A_\ell = S_{h+1}.$$

Proof: Let $\varphi_h(e_i) = A_h(e_i) + \dots + A_m(e_i) - A_h^*(e_i)$. From Eqs. (1) and (2), we have that

$$\varphi_h(e_i) = \sum_{\ell=h}^m \{\delta_\ell(e_i) + q_\ell(e_i)\} - \{\delta_h^*(e_i) + q_h^*(e_i)\}.$$

By induction on events e_i for $i \geq 0$, we show that $\varphi_h(e_i) \geq 0$.

Base Step: For the initial event e_0 , it is immediate that $\delta_h(e_0) = \dots = \delta_m(e_0) = 0$, $q_h(e_0) = \dots = q_m(e_0) = 0$, $\delta_h^*(e_0) = 0$, and $q_h^*(e_0) = 0$. This implies that $\varphi_h(e_0) = 0$.

Induction Step: For $t \geq 1$, we assume that $\varphi_h(e_i) \geq 0$ for each $i \in [0, t-1]$. Let us consider the case that e_t is send event and the case that e_t is arrive event.

(e_t : send event) If **Opt** transmits a v_h -packet, then $\delta_h^*(e_t) + q_h^*(e_t) = \delta_h^*(e_{t-1}) + 1 + q_h^*(e_{t-1}) - 1 = \delta_h^*(e_{t-1}) + q_h^*(e_{t-1})$. It is obvious that $\delta_h^*(e_t) + q_h^*(e_t) = \delta_h^*(e_{t-1}) + q_h^*(e_{t-1})$ if **Opt** does not transmits a v_h -packet. For the case that **Greedy** transmits a v_r -packet with $r \in [h, m]$, it is immediate that $\delta_r(e_t) + q_r(e_t) = \delta_r(e_{t-1}) + 1 + q_r(e_{t-1}) - 1 = \delta_r(e_{t-1}) + q_r(e_{t-1})$ and that $\delta_\ell(e_t) + q_\ell(e_t) = \delta_\ell(e_{t-1}) + q_\ell(e_{t-1})$ for each $\ell \in [h, m] \setminus \{r\}$. For the case that **Greedy** transmits a v_r -packet with $r \in [1, h-1]$, it is easy to see that $\delta_\ell(e_t) + q_\ell(e_t) = \delta_\ell(e_{t-1}) + q_\ell(e_{t-1})$ for each $\ell \in [h, m]$. Then from the induction hypothesis, we have that

$$\begin{aligned} \varphi_h(e_t) &= \sum_{\ell=h}^m \{\delta_\ell(e_t) + q_\ell(e_t)\} - \{\delta_h^*(e_t) + q_h(e_t)\} \\ &= \sum_{\ell=h}^m \{\delta_\ell(e_{t-1}) + q_\ell(e_{t-1})\} - \{\delta_h^*(e_{t-1}) + q_h(e_{t-1})\} \\ &= \varphi_h(e_{t-1}) \geq 0. \end{aligned}$$

(e_t : arrive event) Notice that $\delta_h(e_t) = \delta_h(e_{t-1}), \dots, \delta_m(e_t) = \delta_m(e_{t-1})$ and $\delta_h^*(e_t) = \delta_h^*(e_{t-1})$. Let us consider the following cases: (1) a v_r -packet with $r \in [1, h-1]$ arrives, (2) a v_r -packet with $r \in [h+1, m]$ arrives, and (3) a v_h -packet arrives. For the case (1), it is immediate that $q_h(e_t) = q_h(e_{t-1}), \dots, q_m(e_t) = q_m(e_{t-1})$ and $q_h^*(e_t) = q_h^*(e_{t-1})$. From the induction hypothesis, it follows that $\varphi_h(e_t) = \varphi_h(e_{t-1}) \geq 0$. For the case (2), we have that $q_r(e_t) \geq q_r(e_{t-1}), q_\ell(e_t) = q_\ell(e_{t-1})$ for each $\ell \in [h, m] \setminus \{r\}$, and $q_h^*(e_t) = q_h^*(e_{t-1})$. Thus from the induction hypothesis, it follows that $\varphi_h(e_t) \geq \varphi_h(e_{t-1}) \geq 0$. For the case (3), let us consider the following subcases: (3.1) **Greedy** and **Opt** accept the v_h -packet, (3.2) **Greedy** and **Opt** reject the v_h -packet, (3.3) **Greedy** accepts the v_h -packet but **Opt** rejects the v_h -packet, (3.4) **Greedy** rejects the v_h -packet but **Opt** accepts the v_h -packet. For the subcase (3.1), it is immediate that $q_h(e_t) = q_h(e_{t-1}) + 1, q_\ell(e_t) = q_\ell(e_{t-1})$ for each $\ell \in [h+1, m]$, and $q_h^*(e_t) = q_h^*(e_{t-1}) + 1$. From the induction hypothesis, it follows that $\varphi_h(e_t) = \varphi_h(e_{t-1}) \geq 0$. For the subcase (3.2), we can show that $\varphi_h(e_t) = \varphi_h(e_{t-1}) \geq 0$ in a way similar to the subcase (3.1). For the subcase (3.3), we have that $q_h(e_t) = q_h(e_{t-1}) + 1, q_\ell(e_t) = q_\ell(e_{t-1})$ for each $\ell \in [h+1, m]$, and $q_h^*(e_t) = q_h^*(e_{t-1})$. From the induction hypothesis, it follows that $\varphi_h(e_t) = \varphi_h(e_{t-1}) + 1 \geq 0$. For the subcase (3.4), we have that the v_h -queue of **Greedy** is full, i.e., $q_h(e_t) = B_h$. From the fact that $B_h \geq q_h^*(e_t)$, it is obvious that $q_h^*(e_t) \leq q_h(e_t) \leq q_h(e_t) + \dots + q_m(e_t)$. So from Lemma 3.1 and the definition of φ_h , we have that $\varphi_h(e_t) \geq 0$. ■

4 Competitive Ratio of the Algorithm Greedy

From Lemmas 2.1 and 3.2, it follows that for each $h \in [1, m-2]$,

$$\sum_{\ell=h}^{m-1} D_\ell = \sum_{\ell=h}^m D_\ell \leq \sum_{\ell=h}^m A_\ell = S_h. \quad (3)$$

For each $h \in [1, m-1]$, we derive the $m-h$ upper bounds for $D_h + D_{h+1} + \dots + D_{m-1}$ by applying Eq. (3) and Lemma 3.3 (see an example given in Appendix A). For each $j \in [h, m-3]$, apply Lemma 3.3 to $D_h, D_{h+1}, \dots, D_j$ and apply Eq. (3) to $D_{j+1} + D_{j+2} + \dots + D_{m-1}$, i.e.,

$$\begin{aligned} D_h + D_{h+1} + \dots + D_{m-1} &\leq S_{h+1} + S_{h+1}; \\ D_h + D_{h+1} + \dots + D_{m-1} &\leq S_{h+1} + S_{h+2} + S_{h+2}; \\ &\vdots \\ D_h + D_{h+1} + \dots + D_{m-1} &\leq S_{h+1} + S_{h+2} + \dots + S_{j+1} + S_{j+1}; \\ &\vdots \\ D_h + D_{h+1} + \dots + D_{m-1} &\leq S_{h+1} + S_{h+2} + \dots + S_{m-2} + S_{m-2}. \end{aligned}$$

Applying Lemma 3.3 to $D_h, D_{h+1}, \dots, D_{m-1}$, we have that

$$D_h + D_{h+1} + \dots + D_{m-1} \leq S_{h+1} + S_{h+2} + \dots + S_m,$$

and applying Eq. (3) to $D_h + D_{h+1} + \dots + D_{m-1}$, we also have that

$$D_h + D_{h+1} + \dots + D_{m-1} \leq S_h.$$

Let U_h be the minimum among $m-h$ upper bounds for $D_h + D_{h+1} + \dots + D_{m-1}$. From the definition of U_h , it is immediate that $U_{m-1} = A_m$. For m nonnegative packet values $0 < v_1 < v_2 <$

$\dots < v_m$, let $\mathcal{C}_m = \{c_1, c_2, \dots, c_{m-1}\}$, where for each $i \in [1, m-1]$,

$$c_i = \frac{v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}}{v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}}.$$

Let $c_m^* = \max\{c_1, c_2, \dots, c_{m-1}\}$. Note that $c_m^* < 1$. The following lemmas hold for c_m^* and U_h .

Lemma 4.1: *For each $i \in [1, m-1]$, the following holds:*

$$\left(v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j} \right) - c_m^* \left(v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j} \right) \leq 0.$$

Lemma 4.2: *For each $h \in [1, m-2]$, $U_h = \min\{A_h, U_{h+1}\} + S_{h+1}$, where $U_{m-1} = A_m$.*

The proof of Lemma 4.1 is given in Subsection 5.1 and the proof of Lemma 4.2 is given in Subsection 5.2. For each $h \in [1, m-2]$, define Δ_h as follows:

$$\begin{aligned} \Delta_h &= \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_h \\ &\quad + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right\} S_h \\ &\quad + (v_{h+1} - v_h)U_{h+1} + (v_{h+2} - v_{h+1})U_{h+2} + \dots + (v_{m-1} - v_{m-2})U_{m-1}. \end{aligned}$$

The following lemmas are crucial to analyze the competitive ratio of the algorithm **Greedy**.

Lemma 4.3: *For each $h \in [1, m-3]$, $\Delta_h \leq c_m^* v_h A_h + \Delta_{h+1}$.*

Lemma 4.4: $\Delta_{m-2} \leq c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m$.

The proof of Lemma 4.3 is given in Subsection 5.3 and the proof of Lemma 4.4 is given in Subsection 5.4. From Lemmas 4.2, 4.3, and 4.4, we can show the following theorem:

Theorem 4.1: *For the general m -valued case with class segregation, the online (multi-queue) buffer management algorithm **Greedy** is $(1 + c_m^*)$ -competitive.*

Proof: For any sequence σ , it is immediate that

$$\begin{aligned} \frac{\text{Opt}(\sigma)}{\text{Greedy}(\sigma)} &= \frac{v_1 A_1^* + v_2 A_2^* + \dots + v_m A_m^*}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\ &= 1 + \frac{v_1(A_1^* - A_1) + v_2(A_2^* - A_2) + \dots + v_{m-1}(A_{m-1}^* - A_{m-1}) + v_m(A_m^* - A_m)}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\ &= 1 + \frac{v_1 D_1 + v_2 D_2 + \dots + v_{m-1} D_{m-1}}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m}, \end{aligned}$$

where the last equality follows from Lemma 3.2. We bound $v_1 D_1 + v_2 D_2 + \dots + v_{m-1} D_{m-1}$.

$$\begin{aligned} &v_1 D_1 + v_2 D_2 + \dots + v_{m-1} D_{m-1} \\ &= v_1(D_1 + D_2 + \dots + D_{m-1}) + (v_2 - v_1)(D_2 + D_3 + \dots + D_{m-1}) \\ &\quad + (v_3 - v_2)(D_3 + D_4 + \dots + D_{m-1}) + \dots + (v_{m-1} - v_{m-2})D_{m-1} \\ &\leq v_1 U_1 + (v_2 - v_1)U_2 + (v_3 - v_2)U_3 + \dots + (v_{m-1} - v_{m-2})U_{m-1} \\ &= \Delta_1, \end{aligned}$$

where the inequality follows from $D_h + D_{h+1} + \dots + D_{m-1} \leq U_h$ for each $h \in [1, m-1]$, and the last equality follows from the definition of Δ_h . By the iterative use of Lemma 4.3, we have that

$$\begin{aligned}
\frac{\text{Opt}(\sigma)}{\text{Greedy}(\sigma)} &\leq 1 + \frac{\Delta_1}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\
&\leq 1 + \frac{c_m^* v_1 A_1 + \Delta_2}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\
&\leq 1 + \frac{c_m^* v_1 A_1 + c_m^* v_2 A_2 + \Delta_3}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\
&\vdots \\
&\leq 1 + \frac{c_m^* v_1 A_1 + c_m^* v_2 A_2 + \dots + c_m^* v_{m-3} A_{m-3} + \Delta_{m-2}}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\
&\leq 1 + \frac{c_m^* v_1 A_1 + c_m^* v_2 A_2 + \dots + c_m^* v_m A_m}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\
&= 1 + c_m^* \cdot \frac{v_1 A_1 + v_2 A_2 + \dots + v_m A_m}{v_1 A_1 + v_2 A_2 + \dots + v_m A_m} \\
&= 1 + c_m^*,
\end{aligned}$$

where all inequalities except for the first and last ones follow from Lemma 4.3 and the last inequality follows from Lemma 4.4. Thus Greedy is $(1 + c_m^*)$ -competitive. $\blacksquare$

5 Proofs of Lemmas

5.1 Proof of Lemma 4.1

From the definition of c_i , it follows that for each $i \in [1, m-1]$,

$$\begin{aligned}
&\left(v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j} \right) - c_m^* \left(v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j} \right) \\
&= \left(v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j} \right) \left(\frac{v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}}{v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}} - c_m^* \right) \\
&= \left(v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j} \right) (c_i - c_m^*) \leq 0,
\end{aligned}$$

where the inequality follows from the fact that $c_i \leq c_m^*$ for each $i \in [1, m-1]$.

5.2 Proof of Lemma 4.2

It is obvious that $U_{m-1} = A_m$. From the definition of U_h , it follows that for each $i \in [1, m-2]$,

$$\begin{aligned}
U_{m-(i+1)} &= \min \{ S_{m-i} + U_{m-i}, S_{m-(i+1)} \} = \min \{ S_{m-i} + U_{m-i}, A_{m-(i+1)} + S_{m-i} \} \\
&= \min \{ A_{m-(i+1)}, U_{m-i} \} + S_{m-i}.
\end{aligned}$$

Thus for each $h \in [1, m-2]$ we have that $U_h = \min \{ A_h, U_{h+1} \} + S_{h+1}$.

5.3 Proof of Lemma 4.3

From Lemma 4.2, we have that $U_h = \min\{A_h, U_{h+1}\} + S_{h+1}$ for each $h \in [1, m-2]$. Let us consider the following cases: (1) $A_h \leq U_{h+1}$ and (2) $A_h > U_{h+1}$.

For the case (1), we have that $U_h = \min\{A_h, U_{h+1}\} + S_{h+1} = A_h + S_{h+1} = S_h$. So from the definition of Δ_h and the fact that $U_h = S_h$, it follows that

$$\begin{aligned}
\Delta_h &= \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} S_h \\
&\quad + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right\} S_h \\
&\quad + (v_{h+1} - v_h)U_{h+1} + (v_{h+2} - v_{h+1})U_{h+2} + \cdots + (v_{m-1} - v_{m-2})U_{m-1} \\
&= \left\{ \left(v_h + v_{h-1} + 2 \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + 2 \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} S_h \\
&\quad + (v_{h+1} - v_h)U_{h+1} + (v_{h+2} - v_{h+1})U_{h+2} + \cdots + (v_{m-1} - v_{m-2})U_{m-1} \\
&= \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} (A_h + S_{h+1}) \\
&\quad + (v_{h+1} - v_h)U_{h+1} + (v_{h+2} - v_{h+1})U_{h+2} + \cdots + (v_{m-1} - v_{m-2})U_{m-1} \\
&= \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} A_h \\
&\quad + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
&\quad + (v_{h+1} - v_h)U_{h+1} + (v_{h+2} - v_{h+1})U_{h+2} + \cdots + (v_{m-1} - v_{m-2})U_{m-1} \\
&= c_m^* v_h A_h + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) \right\} A_h \\
&\quad + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
&\quad + (v_{h+1} - v_h)U_{h+1} + (v_{h+2} - v_{h+1})U_{h+2} + \cdots + (v_{m-1} - v_{m-2})U_{m-1} \\
&\leq c_m^* v_h A_h + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) \right\} U_{h+1} \\
&\quad + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
&\quad + (v_{h+1} - v_h)U_{h+1} + (v_{h+2} - v_{h+1})U_{h+2} + \cdots + (v_{m-1} - v_{m-2})U_{m-1} \\
&= c_m^* v_h A_h + \left\{ \left(v_{h+1} + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) \right\} U_{h+1} \\
&\quad + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
&\quad + (v_{h+2} - v_{h+1})U_{h+2} + (v_{h+3} - v_{h+2})U_{h+3} + \cdots + (v_{m-1} - v_{m-2})U_{m-1}
\end{aligned}$$

$$= c_m^* v_h A_h + \Delta_{h+1},$$

where the inequality follows from the fact that $c_m^* < 1$ and the assumption that $A_h \leq U_{h+1}$.

For the case (2), we have that $U_h = \min\{A_h, U_{h+1}\} + S_{h+1} = U_{h+1} + S_{h+1}$. So from the definition of Δ_h and the fact that $U_h = U_{h+1} + S_{h+1}$, it follows that

$$\begin{aligned}
\Delta_h &= \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} (U_{h+1} + S_{h+1}) \\
&\quad + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right\} S_h \\
&\quad + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
&= \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_{h+1} \\
&\quad + \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} S_{h+1} \\
&\quad + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right\} (A_h + S_{h+1}) \\
&\quad + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
&= \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_{h+1} \\
&\quad + \left\{ \left(v_h + v_{h-1} + 2 \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + 2 \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} S_{h+1} \\
&\quad + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right\} A_h \\
&\quad + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
&= \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_{h+1} \\
&\quad + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
&\quad + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right\} A_h \\
&\quad + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
&= \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_{h+1} \\
&\quad + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1}
\end{aligned}$$

$$\begin{aligned}
& + c_m^* v_h A_h + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} A_h \\
& + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
\leq & \left\{ \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_{h+1} \\
& + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
& + c_m^* v_h A_h + \left\{ \left(v_{h-1} + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_h + \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_{h+1} \\
& + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
= & \left\{ \left(v_h + v_{h-1} + 2 \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) - c_m^* \left(v_h + v_{h-1} + 2 \sum_{j=1}^{h-2} 2^{j-1} v_{h-1-j} \right) \right\} U_{h+1} \\
& + c_m^* v_h A_h + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
& + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
= & c_m^* v_h A_h + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) \right\} U_{h+1} \\
& + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
& + (v_{h+1} - v_h) U_{h+1} + (v_{h+2} - v_{h+1}) U_{h+2} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
= & c_m^* v_h A_h + \left\{ \left(v_{h+1} + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) \right\} U_{h+1} \\
& + \left\{ \left(v_h + \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right) - c_m^* \sum_{j=1}^{h-1} 2^{j-1} v_{h-j} \right\} S_{h+1} \\
& + (v_{h+2} - v_{h+1}) U_{h+2} + (v_{h+3} - v_{h+2}) U_{h+3} + \cdots + (v_{m-1} - v_{m-2}) U_{m-1} \\
= & c_m^* v_h A_h + \Delta_{h+1},
\end{aligned}$$

where the inequality follows from Lemma 4.1 for $i = h - 1$ and the assumption that $A_h > U_{h+1}$.

5.4 Proof of Lemma 4.4

From Lemma 4.2, it follows that $U_{m-2} = \min\{A_{m-2}, U_{m-1}\} + S_{m-1} = \min\{A_{m-2}, A_m\} + A_{m-1} + A_m$. Let us consider the following cases: (1) $A_{m-2} \leq A_m$ and (2) $A_{m-2} > A_m$.

For the case (1), we have that $U_{m-2} = A_{m-2} + A_{m-1} + A_m = S_{m-2}$. So from the definition of Δ_{m-2} and the fact that $U_{m-2} = S_{m-2}$, it follows that

$$\Delta_{m-2} = \left\{ \left(v_{m-2} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} S_{m-2}$$

$$\begin{aligned}
& + \left\{ \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right\} S_{m-2} \\
& + (v_{m-1} - v_{m-2}) A_m \\
= & \left\{ \left(v_{m-2} + v_{m-3} + 2 \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + 2 \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} S_{m-2} \\
& + (v_{m-1} - v_{m-2}) A_m \\
= & \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right\} (A_{m-2} + A_{m-1} + A_m) \\
& + (v_{m-1} - v_{m-2}) A_m \\
= & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_{m-2} \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_{m-1} \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_m + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_m \\
& + (v_{m-1} - v_{m-2}) A_m \\
\leq & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_m \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_{m-1} \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_m + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_m \\
& + (v_{m-1} - v_{m-2}) A_m \\
= & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m \\
& + \left\{ \left(v_{m-1} + \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right) - c_m^* \left(v_m + \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right) \right\} A_m \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_{m-1} \\
= & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m \\
& + \left(v_m + \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right) (c_{m-1} - c_m^*) A_m \\
& + \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) (c_{m-2} - c_m^*) A_{m-1} \\
\leq & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m,
\end{aligned}$$

where the first inequality follows from the fact $c_m^* < 1$ and the assumption that $A_{m-2} \leq A_m$ and the second inequality follows from Lemma 4.1 for $i = m - 1$ and $i = m - 2$.

For the case (2), we have that $U_{m-2} = A_{m-1} + 2A_m$. Then from the definition of Δ_{m-2} and the fact that $U_{m-2} = A_{m-1} + 2A_m$, it follows that

$$\begin{aligned}
\Delta_{m-2} &= \left\{ \left(v_{m-2} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} (A_{m-1} + 2A_m) \\
&\quad + \left\{ \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right\} (A_{m-2} + A_{m-1} + A_m) \\
&\quad + (v_{m-1} - v_{m-2}) A_m \\
&= \left\{ \left(v_{m-2} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} (A_{m-1} + A_m) \\
&\quad + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} A_m \\
&\quad + \left\{ \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right\} (A_{m-1} + A_m) \\
&\quad + \left\{ \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right\} A_{m-2} \\
&\quad + (v_{m-1} - v_{m-2}) A_m \\
&= \left\{ \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right\} A_{m-2} \\
&\quad + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right\} (A_{m-1} + A_m) \\
&\quad + \left\{ \left(v_{m-1} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} A_m \\
&= c_m^* v_{m-2} A_{m-2} + \left\{ \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-2} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} A_{m-2} \\
&\quad + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right\} A_{m-1} \\
&\quad + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right\} A_m \\
&\quad + \left\{ \left(v_{m-1} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} A_m \\
&\leq c_m^* v_{m-2} A_{m-2} + \left\{ \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-2} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} A_m
\end{aligned}$$

$$\begin{aligned}
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right\} A_{m-1} \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right\} A_m \\
& + \left\{ \left(v_{m-1} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) - c_m^* \left(v_{m-3} + \sum_{j=1}^{m-4} 2^{j-1} v_{m-3-j} \right) \right\} A_m \\
= & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_{m-1} \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right\} A_m \\
& + \left\{ \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-2} + 2 \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_m \\
= & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_{m-1} \\
& + \left\{ \left(v_{m-1} + \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right) - c_m^* \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right\} A_m \\
= & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m \\
& + \left\{ \left(v_{m-2} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) - c_m^* \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) \right\} A_{m-1} \\
& + \left\{ \left(v_{m-1} + \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right) - c_m^* \left(v_m + \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right) \right\} A_m \\
= & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m \\
& + \left(v_{m-1} + \sum_{j=1}^{m-3} 2^{j-1} v_{m-2-j} \right) (c_{m-2} - c_m^*) A_{m-1} \\
& + \left(v_m + \sum_{j=1}^{m-2} 2^{j-1} v_{m-1-j} \right) (c_{m-1} - c_m^*) A_m \\
\leq & c_m^* v_{m-2} A_{m-2} + c_m^* v_{m-1} A_{m-1} + c_m^* v_m A_m,
\end{aligned}$$

where the first inequality follows from Lemma 4.1 for $i = m-3$ and the assumption that $A_{m-2} > A_m$ and the second inequality follows from Lemma 4.1 for $i = m-2$ and $i = m-1$.

6 Concluding Remarks

In this paper, we have focused on multi-queue buffer management with class segregation. In particular, we have dealt with the general m -valued case (packet values are $0 < v_1 < v_2 < \dots < v_m$)

and have shown (in Theorem 4.1) that **Greedy** is $(1 + c_m^*)$ -competitive, where $c_m^* = \max_i c_i$ and

$$c_i = \frac{v_i + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}}{v_{i+1} + \sum_{j=1}^{i-1} 2^{j-1} v_{i-j}}$$

for each $i \in [1, m-1]$. Al-Bawani and Souza [2, Theorem 3.1] showed that for the general-valued case, the competitive ratio of any deterministic online algorithm is at least

$$2 - \frac{v_m}{v_m + v_{m-1} + \dots + v_1} = 1 + \frac{v_{m-1} + \dots + v_1}{v_m + v_{m-1} + \dots + v_1}.$$

For the general m -valued case, it is immediate that

$$1 + c_m^* \geq 1 + c_{m-1} > 1 + \frac{v_{m-1} + \dots + v_1}{v_m + v_{m-1} + \dots + v_1},$$

which implies that there might be gap between the lower and upper bounds for the competitive ratio of the algorithm **Greedy**. To precisely capture the inherent nature of the multi-queue buffer management with class segregation, the following problems are left to solve.

- (1) Design an efficient online (multi-queue) buffer management algorithm for the general m -valued case to improve the upper bound of the competitive ratio.
- (2) Improve the lower bound of the competitive ratio for the general m -valued case.

References

- [1] W.A. Aiello, Y. Mansour, S. Rajagopalan, and A. Rosen. Competitive Queue Policies for Differential Services. In *Proc. of IEEE INFOCOM*, pp.431–440 (2000).
- [2] L. Al-Bawani and A. Souza. Competitive Buffer Management with Class Segregation. arXiv:1103.6049v2 [cs.DS] 30 Mar 2011.
- [3] S. Albers and M. Schmidt. On the Performance of Greedy Algorithms in Packet Buffering. In *Proc. of the 36th Annual ACM Symposium on Theory of Computing* pp.35–44 (2004).
- [4] Y. Azar. Online packet Switching. In *Proc. of the 2nd Workshop on Approximation and Online Algorithms*, Lecture Notes in Computer Science 3351, pp.1-5 (2004).
- [5] Y. Azar and A. Litichevsky. Maximizing Throughput in Multi-Queue Switches. In *Proc. of the 12th European Symposium on Algorithms*, Lecture Notes in Computer Science 3221, pp.53-64 (2004).
- [6] Y. Azar and Y. Richter. Management of Multi-Queue Switches in QoS Networks. In *Proc. of the 35th Annual ACM Symposium on Theory of Computing*, pp.82–89 (2003).
- [7] Y. Azar and Y. Richter. The Zero-One Principle for Switching Networks. In *Proc. of the 36th Annual ACM Symposium on Theory of Computing*, pp.64–71 (2004).
- [8] A. Borodin and R. El-Yaniv. Online Computation and Competitive Analysis. Cambridge University Press (1998).

- [9] M. Bienkowski and A. Mardy. Geometric Aspects of Online Packet Buffering: An Optimal Randomized Algorithm for Twp Buffers. In *Proc. of the 8th Latin American Symposium on Theoretical Informatics*, Lecture Notes in Computer Science ,4857 pp.252-263 (2008).
- [10] M. Chrobak. Online Algorithms Column 13. *ACM SIGACT News*, Volume 39, Issue 3, pp.96-121 (2008).
- [11] Cisco Systems, Inc. Quality of Service (QoS). Internetworking Technology Handbook, Chapter 49, 2006.
- [12] L. Epstein and R. van Stee. Buffer Management Problems. *ACM SIGACT News*, Volume 35, Issue 3, pp.58-66 (2004).
- [13] M.H. Goldwasser. A Survey of Buffer Management Policies for Packet Switches. *ACM SIGACT News*, Volume 41, Issue 1, pp.100-128 (2010).
- [14] T. Itoh and N. Takahashi. Competitive Analysis of Multi-Queue Preemptive QoS Algorithms for General Priorities. *IEICE Trans. on Fundamentals of Electronics, Communications, and Computer Science*, Vo.E89-A, No.5, pp.1186-1197 (2006).
- [15] W. Jawor. Three Dozen Papers on Online Algorithmms. *ACM SIGACT News*, Volume 36, Issue 1, pp.71-85 (2004).
- [16] A. Kesselman, Z. Lotker, Y. Mansour, B. Patt-Shamir, B. Schieber, and M. Sviridenko. Buffer Overflow Management in QoS Switches. In *Proc. of the 33rd Annual ACM Symposium on Theory of Computing*, pp.520–529 (2001).
- [17] G. Li and H. Liu. Dynamic Resource Allocation with Finite Buffer Constraints in Broad-band OFDMA Networks. In *Proc. of IEEE Wireless Communications and Networking Conference*, pp.1037-1042, 2003.
- [18] Y. Mansour, B. Patt-Shamir, and O. Lapid. Optimal Smoothing Schedules for Real-Time Streams. In *Proc. of of the 19th ACM Symposium on Principles of Distributed Computing*, pp.21.29 (2000).

A An Example

Let $m = 5$. From Lemma 3.3 and Eq. (3), we have the following inequalities.

$$D_1 \leq S_2 \tag{4}$$

$$D_2 \leq S_3 \tag{5}$$

$$D_3 \leq S_4 \tag{6}$$

$$D_4 \leq S_5 \tag{7}$$

$$D_1 + D_2 + D_3 + D_4 \leq S_1 \tag{8}$$

$$D_2 + D_3 + D_4 \leq S_2 \tag{9}$$

$$D_3 + D_4 \leq S_3 \tag{10}$$

For $D_1 + D_2 + D_3 + D_4$, we have the following four upper bounds:

$$\begin{aligned}
D_1 + D_2 + D_3 + D_4 &\leq S_2 + S_2; && \text{from Ineqs. (4) and (9)} \\
D_1 + D_2 + D_3 + D_4 &\leq S_2 + S_3 + S_3; && \text{from Ineqs. (4), (5), and (10)} \\
D_1 + D_2 + D_3 + D_4 &\leq S_2 + S_3 + S_4 + S_5; && \text{from Ineqs. (4), (5), (6), and (7)} \\
D_1 + D_2 + D_3 + D_4 &\leq S_1. && \text{from Ineq. (8)}
\end{aligned}$$

For $D_2 + D_3 + D_4$, we also have the following three upper bounds.

$$\begin{aligned}
D_2 + D_3 + D_4 &\leq S_3 + S_3; && \text{from Ineqs. (5) and (10)} \\
D_2 + D_3 + D_4 &\leq S_3 + S_4 + S_5; && \text{from Ineqs. (5), (6), and (7)} \\
D_2 + D_3 + D_4 &\leq S_2. && \text{from Ineq. (9)}
\end{aligned}$$

For $D_3 + D_4$, we also have the following two upper bounds.

$$\begin{aligned}
D_3 + D_4 &\leq S_4 + S_5; && \text{from Ineqs. (6) and (7)} \\
D_3 + D_4 &\leq S_3, && \text{from Ineq. (10)}
\end{aligned}$$

and we finally have that $D_4 \leq S_5$.